2020 Nissan GT-R NISMO Specifications (EU)

Specifications are based on latest product information available at the time of printing

Mechanical

Engine	
Designation	VR38DETT
Cam configuration	DOHC
Orientation	Longitudinal
Cylinders / configuration	V6
Block / head composition	Aluminum/Aluminum
Displacement (liters)	38
Horsepower	441kW (600ps) @ 6,800 RPM1
Torque Nm	652Nm @ 3,600 - 5,600 RPM1
Bore & stroke (mm)	95.5 x 88.4 (Plasma sprayed bore)
Compression ratio (:1)	90
Maximum engine speed	7,100 RPM
Fuel delivery system	Sequential multi-point electronic fuel ir
Valvetrain	4 valves per cylinder, CVTCS
Turbocharger	High-efficiency High-capacity NISMO G
Turbocharger	svstem
Engine mounts	2 liquid-filled, front; 1 solid, rear
Recommended fuel	Premium unleaded, 100 octane
	3-way catalyst and secondary air inject
Emissions system	3-way catalyst and secondary all inject
Emission certification level	EPA Tier 2-Bin5 (Euro 6B)
Exhaust	Dual system, 4 outlets (2 each side)
	with burnished tips and Exhaust \$
	with burnished tips and Exhaust t
Electrical	
Ignition system	Electronic, Nissan Direct Ignition System
	, , ,
Starter	12V
Alternator	150 Amp.
Battery	12V - 65B24(S)-HR/52 Ah
Transmission and Drive System	
Drive configuration	Mid-mounted front engi
	rear transaxle ATTESA E-TS all-
Transmission	Dual clutch sequential 6-speed rear tra
	shifters, gear pre-selection
Gear ratio 1st	4,056
2nd	2.301
	2.501
3rd	1.595
4th	1.248
5th	1.001
6th	796
Reverse	3.383
Final drive ratio	Front: 2.937, Rear: 3.700
Driveshafts	Carbon composite
Manual/Automatic modes	S
Configurable Shift Control	S
Downshift Rev Matching (DRM)	S
1.5-way mechanical limited slip differential	S
Traction Control System with Limited Slip	S
Vehicle Dynamic Control (VDC)	S
Save-mode function	
Hill Start Assist (HSA)	S
I IIII Ceare / 10010c (110/1)	

Variable Familia de Carterel (ATTECA E TC)	
Yaw Rate Feedback Control (ATTESA E-TS)	S
Brakes Carbon ceramic brake system: Brembo® carbon	S
ceramic rotors and calipers	
Front Type	Brembo® six piston monoblock calipe
Rotor size diameter and thickness (mm)	vented and drilled rote
Trotor Size diameter and thickness (min)	410 x 38
Rear Type	Brembo® four piston monoblock calip
Rotor size diameter and thickness (mm)	vented and drilled roto
Trotor size diameter and emericos (mm)	390 x 32
Brake control	Active power brake booster (double)
Anti-lock Brake System (ABS)	S
Number of wheels	4
Number of channels	4
Number of sensors	4
Electronic Brake force Distribution (EBD)	S
Brake Assist	S
Parking brake	Hand-operated
Brake cooling air guide (front and rear)	S
Steering	
Туре	Vehicle speed-sensitive power rack-and
O	steering rack, four-point mounting
Overall ratio	15:1
Turns (lock to lock) Turning diameter (meter)	122
Steering wheel	3-spoke Alcantara®-wrapped with air b
	telescoping, lap timer switch
NISMO Dark Gray steering wheel with red stripe and	S
Alcantara® accents	
Steering wheel ASCD, audio and Bluetooth® Lap time	S
switches	
Suspension	
NISMO-tuned suspension with unique shock absorber	S
settings and spring rates	
Front	Independent double wishbone alumini
	frame structure, six-point m
Rear	Independent multi-link aluminum sus
	tube-frame structure, six-point mou
	upper/lower links
1	
Large-diameter (34 mm) hollow front stabilizer bar	S
Large diameter (17.2 mm) hollow room stabilizer har	S
Large-diameter (17.3 mm) hollow rear stabilizer bar	5
Bilstein® DampTronic mono-tube shock absorbers,	S
· ·	5
computer controlled, 3-position	
driver adjustable Linear springs (Front); Progressive springs (Rear)	S
Linear springs (Fronc), Progressive springs (Rear)	
High-accuracy alignment, fully adjustable	S
Body / Chassis	
Type	Unibody
Materials (primary)	Steel, carbon fiber, die-cast aluminum
Additional body bonding	S
Platform	Premium-Midship (PM)

Exterior

LATERIO	
Wheels & Tires	
Wheels F: 20x10.0 inches, R: 20x10.5 in.	S
Lightweight 9-spoke RAYS® aluminum-alloy forged,	S
black finish	
Tires Dunlop® SP Sport Maxx GT600 ultra high	S
performance run-flat	
tires F: 255/40ZRF20 XL	
, R: 285/35ZRF20 XL	
NISMO-specific compound	
·	
Tire Pressure Monitoring System (TPMS), pressure and	S
position shown on multi- function meter	
position shown on mater randeron meter	
Lights	
Headlights LED	S
Integrated LED daytime	S
running lights	
Auto on/off	
Taillights "GT-R" 4-ring LED	SS
Spoiler-mounted LED center high-	
mount stop lamp	
Exterior Features	
NISMO aerodynamic package with unique carbon fiber	S
front and rear bumpers, Black outside mirrors with red	
stripe, carbon fiber side sill covers	
Carbon fiber roof, hood and front fenders with air	S
vents	
Functional rear underbody diffuser	Carbon fiber
Carbon fiber rear spoiler2	S
Front spoiler with carbon fiber air duct	S
Carbon fiber trunk lid	S
Front "aero-blade" fenders with vents	S
Aerodynamic front underbody cover	S
Integrated, flush mounted aluminum door handles	S
UV-filtering front and rear side glass, laminated UV-	S
reducing windshield	
Folding side mirrors, power/power folding, heated	S
Body-color bumpers	S
Dark Gray grille	S
Aerodynamic flat-blade windshield wipers, variable	S
intermittent, speed-sensitive	
intermittent, sbeed-sensitive	

Interior

Seating	
Capacity	4 passengers
Front Seat Type	Bucket, sport style, with accommodatic
	safety harness
NISMO-exclusive Recaro® leather-appointed front	S
seats with red stitching	
Red seat backs, shift knob, door grip	S
Leather/synthetic suede front seat appointments	S

Driver's seat	2-way power		S
Front Passenger's seat 2-way power			S
Instrumentation			
Meters/gauges Speedometer T	achometer	9	S
Coolant temperature			
Fuel level			
LCD dual trip odometer			
Red-accented tachometer			 S
Multi-Function Display system	featuring: Turbo boost		<u>5</u> S
Water temp			
Engine temp and oil pressure	Transmission oil temp		
and pressure	ransmission on temp		
F. 555 a. 5			
Speed, Accel, Braking		9	S
Accel G/ Braking G/ Cornering	G/ Accel braking G/	9	S
Fuel level, flow and economy	. <u> </u>		S
Front to rear drive dist. (torqu	e split) Steering position	9	S
Brake and accelerator position	, ,		S
Convenience Features			
RearView Monitor Cruise contr	ol (ASCD)	9	S
Power windows – driver and pa	assenger one-		
touch up/down Power door loc	ks		
Remote keyless entry system	Intelligent key system		
Cupholders - 3	- , ,		
12-volt outlets – 2			
Sunvisors w/ vanity mirrors ar	nd lamps Inside rear		
view mirror – auto-dimming M	ap light, door step lamp		
Center console storage area A			
dual zone	,		
3-position setup switches for s	uspension, transmission		
and VDC	•		
Carbon fiber interior trim			
Active Sound Enhancement (A	SE)		
, i	-		

Safety and Security

Passenger Restraint System	
Nissan Advanced Air Bag System (AABS)	Driver and front passenger air bags wit
	inflation and seat belt sensors
Seat belts, front and rear	3-point (ELR for passengers, ELR for dr
Front seatbelts w/pre-tensioners and load limiters	S
Power window lockout button	S
Rear seat upper and lower tether anchors	S
Impact Safety	

Zone Body Construction with front and rear crumple	S	
zones		
Energy-absorbing steering column Hood buckling		
creases		
High-strength side door guard beams		
Security		
Tamper proof door lock key cylinder Vehicle Security	S	
System (VSS) Immobilizer		
System (VSS) Immobilizer		
Dimensions	•	
Exterior (mm)		
Wheelbase	2780)
Overall length	4690	
Overall width	1895	
Overall height	1370	
Track width Front/Rear	1600/1	600
Coefficient of drag (Cd)	26	
Interior (mm)	Front	
Head room	9.682	
Leg room	11.323	
Hip room	13.882	
Shoulder room	13.797	
Weights Comb availabt (Irilla graphs) Front Book To	hall 026	
Curb weight (kilograms) Front Rear To		
	767	
Weight distribution (%) Front/rear	1703 54/40	
GVWR (kg)	2200 (P	
Capacities	2200 (1	1 VV)
Fuel tank (liter)	74	
Engine oil (liter)	62	
Engine coolant w/ reservoir (liter)	117	
Volume (cu. ft)	117	
Passenger compartment	790	
Cargo	88	
Total	878	
Fuel Economy (I/100km)		
(Actual mileage may vary)		
Lo	TBD	
Mid	TBD	
High	TBD	
exHigh	TBD	
TOTAL	TBD	

S- Standard

- O- Optional
- 1. 100 octane gasoline required
- 2. Dry carbon fiber requires specific maintenance. Please see Owner's Manual for details.

-
njection
T3 Twin- Turbo
ion avetare
ion system
Titanium exhaust
Sound Control
em (NDIS)
em (NDIS)
ne /
ne /
ne / wheel drive nsaxle, paddle

ers, full- floating,
ors
715
ers, full- floating,
_
ors
-
1-pinion, aluminum
,
ag, manual tilt and
um intogral tubo
um, integral tube-
nounting
anoncion intogral
spension, integral
nting, aluminum
-

-
on for 4- point

:h d	dual-	sta	ge	
ive	er)			

Dane	
Rear	
8.519	
6 704	
8.519 6.704 11.406 1269	
11.406	
1269	